Applicant: Y. Izumi, et al. U.S.S.N. 08/UNASSIGNED Preliminary Amendment Filed With Application Page 2

Page 1, before line 1 insert the following:

cz

This application is a continuation of co-pending U.S. application serial number 08/618,833, filed March 20, 1996 (now allowed), the teachings of which are incorporated herein by reference.

Page 18, rewrite the paragraph starting at line 13, to read as follows.

N3

at no

For example, a ultraviolet ray hardening resin having the following characteristics may be used. Such a ultraviolet ray hardening resin has (1) a double bond such as acrylic and ene/thiol (polyene/polythiol), the double bond being cleft upon projection of the ultraviolet ray to progress polymerization, and (2) an index of refraction of 1.53 after being hardened.

Page 29, rewrite the paragraph starting at line 11, to read as follows.

Another liquid crystal display device 1 is actually prepared with the width *D* of the connected part between the liquid crystal panels 2 of 100 µm using a resin of a coefficient of elasticity of 2,000kgf/cm² as the bonding agent 9. In the resulting liquid crystal display device 1, cracks or a peeling are not observed around the connected part, and the joint between the liquid crystal panels 2 is not noticeable.

IN THE CLAIMS

Cancel claims 7-13 and 20-26 without prejudice.

Amend claims 1-2 and 4-5 to read as follows:

25

1. (AMENDED) A display device, comprising:

plural display panels, adjoining display panels being connected with each other by means of a bonding agent, so as to have a single display screen,